










Article Kiss T3766

Method of Production	tufted	
Polmaterial	100 % 107	
Loops per unit area approx.	240.950 /m <sup>2</sup>	
Dyeing	Piece dyeing	
Backing material	Synthetics	
Backing	Textile back	
Pile weight approx.	1.850 g/m <sup>2</sup>	
Total weight approx.	2.650 g/m <sup>2</sup>	
Pile height approx.	14 mm	
Total height approx.	16,5 mm	
Delivery width	500 cm	
Repeat length		
Repeat width		
Qualification	    	<p style="text-align: center;"> <b>CE</b>            23            JAB Teppiche            HEINZ ANSTOETZ KG            Dammheider Str. 67            D-32052 Herford-Elverdissen            EN1307            JT-CO-023-02               EN14041:2018-05            Notified Body: 0493            Floor covering to be used within a            building            * In loosely laid condition         </p>
Color fastness / light fastnes	ISO 105-B02: 5-6	
Abrasion resistance wet / dry	ISO 105-X12: 3-4	
Water fastness	ISO 105-E01: 3-4	
Fastness to seawater		
Fastness to chlorine water		
resistance to heat conduction	ISO 8302 : 0,19 m <sup>2</sup> /KW	
Standard of flammability	EN 13501-01 Cfl-s1 In loosely laid condition	
Absorption of step sound	20	
Sound absorption coefficient		
Moth protection		

We reserve the right to make any technical changes which serve to improve the products.

Version: 03.08.2023